




APPLICATIONS

Suitable for illumination of hazardous locations in various industries.


BFC(BFE)8126 LED EXPLOSION-PROTECTED (EMERGENCY) FLOODLIGHT



- Explosion group: IIC
- Degree of protection up to IP66
- Efficiency of luminaire: Over 85%
- Emergency type with duration up to 60 minutes available for ordering
- Low weight and suitable for seat mounting, wall mounting and pendant mounting



DIMENSION DRAWINGS



*all dimensions in mm


Zone 1 or Zone 2

TECHNICAL DATA

| | |
|--------------------------------|--|
| Certification | |
| International approvals | ATEX, SASO, CNEX |
| Coding | II 2G db mb op is IIC T6 Gb II 2G Ex db eb mb IIC T6 Gb |
| Conformity to standards | |
| IEC 60079 / IEC 60598 | |
| Material | |
| Body material | Aluminum alloy with epoxy powder coating |
| Diffuser | Tempered glass |
| Light source | |
| Brand | OSRAM |
| Wattage | 70 W, 100 W |
| Type | LED |
| Luminous efficiency | 140 lm / W |
| Life | 100000 h |
| Rated voltage | |
| 220 V - 240 V AC 50 Hz / 60 Hz | |
| Class of insulation | |
| Class I | |
| Degree of protection | |
| IP 66 | |
| Operating temperature | |
| -20 °C to +55 °C | |
| Cable entry | |
| G3/4 | |
| Corrosion-proof class | |
| WF2 | |
| Driver brand | |
| OKTECH | |
| Country original | |
| China | |


PHOTOMETRIC DATA

BFC8126 70 W / 100 W, BFE8126 70 W
LED photometric data
The data from OSRAM lamp
Luminous intensity distribution cd / 1000 lm



70W

cd / 1000 lm
Ratio of distance to height: 1.2



100W

cd / 1000 lm
Ratio of distance to height: 1.1

We can provide lighting design and data by professional lighting software based upon simulated site situation on request.


SELECTION TABLE

| Model | Lamp power (W) | Lamp type | Operating current (A) | Color temperature (K) | Weight (kg) |
|-----------------|----------------|-----------|-----------------------|-----------------------|-------------|
| BFC8126/70/LED | 70 | LED | 0.7 | 6200 - 7000 | 10.5 |
| BFC8126/100/LED | 100 | LED | 0.7 | 6200 - 7000 | 10.5 |
| BFE8126/70/LED | 70 | LED | 0.7 | 6200 - 7000 | 11 |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |

MOUNTING TYPE


Pendant mount

*all dimensions in mm



| Accessories | | | | |
|-------------|-----------------------------------|--------|------|--------------------------|
| No. | Name | Spec. | Qty. | Remark |
| 1 | Steel pipe | G3/4 | 1 | Provided by user |
| 2 | Slotted set screws with flat head | M4 × 6 | 2 | Provided by manufacturer |
| 3 | Nut connector | G3/4 | 1 | |
| 4 | Sealing ring | Ø14 | 1 | |
| 5 | Sealing ring | Ø10 | 1 | |
| 6 | Sealing ring | Ø12 | 1 | |
| 7 | Washer | Ø14 | 1 | |

Wall mount



| Accessories | | | | |
|-------------|--------------|--------------|------|--------------------------|
| No. | Name | Spec. | Qty. | Remark |
| 1 | Steel plug | 030101-05-04 | 1 | Provided by manufacturer |
| 2 | Sealing ring | 030602-21-Ex | 1 | |
| 3 | Washer | 050703-22 | 2 | |
| 4 | Gland nut | G3/4 | 2 | |
| 5 | Sealing ring | Ø14 | 2 | |
| 6 | Sealing ring | Ø10 | 2 | |
| 7 | Sealing ring | Ø12 | 2 | |

SPARE PARTS

| Name | Picture | Ordering code | Weight (KG) |
|-----------------------------|---------|---------------|-------------|
| Light source - 70 W | / | 1311010269 | / |
| Light source - 100 W | / | 1311020270 | / |
| LED driver - 70 W | / | 3037201023 | / |
| LED driver - 100 W | / | 3037201024 | / |
| Emergency LED driver - 70 W | / | 3037201025 | / |